

Infortrend ESVA® Expansion Units



Each Infortrend ESVA system can be scaled up for increased capacity by connecting it to expansion units through SAS expansion ports. This task can be accomplished in minutes. ESVA's unique modular design can be scaled as needed, thereby minimizing cost wasted on unneeded capacity.

Technical Specifications

	ESVA J60-130	ESVA J60-230
Drive Connectivity	Exclusively 3Gb/s SAS	Exclusively 6Gb/s SAS
Starting No. of Drives	8	
Supported Drives	300, 450 or 600GB - 3.5" 15,000 RPM SAS drives	100GB or 200GB - STEC MACH16 SSD 300, 450 or 600GB - 3.5" 15,000 RPM SAS drives 1TB or 2TB - 3.5" 7,200 RPM Nearline SAS drives 300, 450 or 600GB - 2.5" 10,000 RPM SAS drives
Max. Drive (per system)	16	
Corresponding ESVA Model	ESVA F60-1830	ESVA E60 ESVA F60-2830 ESVA F70
Host Ports	Four (4) 3Gb/s SAS 4x wide ports	Four (4) 6Gb/s SAS 4x wide ports
Redundant Hardware Modules	Controllers, Power Supplies, Cooling Fans	
Form Factor	3U	
Service and Support¹	All ESVA systems are shipped with 3-year Standard Service.	
Standard Service	Hardware warranty; replacement part dispatch on the next business day Software update; 24x7 phone, web and email support	
Advanced Service ²	Standard Service + Onsite diagnostics on the next business day	
Premium Service ²	Standard Service + Onsite diagnostics in 4 hours	

¹Service may vary by region.

²Optional.

24x7 Global Support: <http://support.infortrend.com/esva>