



## NetScalper P710-SLE0 All-Flash Array

## SPECIFICATIONS

<b>Form Factor</b>	2U rack mount	
<b>IOPS @ 4KB Mixed<sup>1</sup></b>	400K	
<b>Flash Management</b>	FlexiRemap <sup>®</sup> technology	
<b>Capacity<sup>2</sup></b>	13TB usable / 69TB effective <sup>3</sup>	
<b>Number of SSDs</b>	24	
<b>SSD Type</b>	SATA	
<b>Connectivity</b>	6 x 10GbE SFP+	
<b>Storage Protocols</b>	iSCSI NFS, CIFS	
<b>Management Interface</b>	Web GUI (HTTP/HTTPS) CLI (serial port)	
<b>Power Supply</b>	920W 1+1 redundant	
<b>Feature Highlights</b>	<ul style="list-style-type: none"> <li>• Outperforming IOPS via mainstream connectivity</li> <li>• Two hot spares</li> <li>• Data protection through redundancy</li> <li>• All software features built in</li> </ul>	
<b>Software Function</b>	<ul style="list-style-type: none"> <li>• Free Clone</li> <li>• Snapshot</li> <li>• Snapshot Backup/Recovery</li> <li>• Remote Replication</li> <li>• Thin Provisioning</li> </ul>	<ul style="list-style-type: none"> <li>• Thick Provisioning</li> <li>• Inline Deduplication</li> <li>• vSphere Web Client Plug-in</li> <li>• RESTful API</li> </ul>
<b>Certification</b>	<ul style="list-style-type: none"> <li>• VMware Ready</li> <li>• VMware VAAI Block</li> </ul>	<ul style="list-style-type: none"> <li>• Microsoft Windows Server 2012 R2</li> <li>• Microsoft Windows Server 2016</li> </ul>
<b>Dimensions (W x D x H)</b>	437mm x 630mm x 89mm (17.2in x 24.8in x 3.5in)	
<b>Net Weight<sup>4</sup></b>	19.8kg (43.7lb)	
<b>Environmental Temperature</b>	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)	
<b>Environmental Humidity</b>	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing	

<sup>1</sup> Based on designated testing conditions. Performance may vary with different applications or product configurations.

<sup>2</sup> Usable capacity refers to the approximation of the storage capacity that users can have. The available usable capacity may vary depending on software configurations and other factors. Effective capacity is less than raw disk capacity.

<sup>3</sup> Weight may vary depending on components and manufacturing variability.

©2015, 2016. All rights reserved. FlexiRemap, and NetScalper are trademarks or registered trademarks of Dell EMC in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. We are continuing effort to improve the quality of our products. Information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. Dell EMC reserves the right to the interpretation of the above specifications, terms and conditions.

