



NeoSapphire

NS3413 All-Flash Array

- Superior performance with 600K IOPS using iSCSI protocol over 10GbE
- Fault-tolerance with 24 hot-swappable SSDs, including 2 for hot spares
- Automatic data reconstruction for peace of mind





NeoSapphire 3605 All-Flash Array

SPECIFICATIONS

Form Factor	2U rack mount
IOPS for 4KB Random Write	600K sustained
Flash Management	FlexiRemap technology
Raw Capacity	21TB
Usable Capacity ¹	13TB
Number of SSD	24 x hot-swappable SSD
Flash Type	MLC
Connectivity	4 x 10GbE SFP+
Storage Protocol	iSCSI NFS, CIFS/SMB
Management Interface	Web-based management interface (via HTTP/HTTPS) CLI (via serial port)
Power Supply	900W 1+1 redundant
Feature Highlight	<ul style="list-style-type: none"> • Outperforming IOPS via mainstream connectivity • Two SSDs for hot spares • Data protection through redundancy
Software Function	<ul style="list-style-type: none"> • Thin Provisioning • Inline Deduplication (Zero Page)
Certification	• VMware Ready
Dimensions (W x D x H)	437mm x 630mm x 89mm (17.2in x 24.8in x 3.5in)
Net Weight ²	19.8kg (43.7lb)
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing

¹ Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.


² Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.



Carl-Zeiss-Str. 27-29 • D-73230 Kirchheim / Teck
Tel. +49(0)7021-487 200 • Fax +49(0)7021-487 400

www.starline.de



VC20170302