



NeoSapphire

NS3501 All-Flash Array

- A low TCO solution offering superior performance with 360K IOPS over InfiniBand FDR connectivity
- Easy maintenance with 8 hot-swappable SSDs and 2 PSUs
- Fault tolerance with automatic data reconstruction for a peace of mind





NeoSapphire 3501 All-Flash Array

SPECIFICATIONS

Form Factor	1U rack mount
IOPS for 4KB Random Write	360K sustained
Flash Management	FlexiRemap technology
Raw Capacity	2TB
Usable Capacity ¹	1TB
Number of SSD	8 x hot-swappable SSD
Flash Type	MLC
Connectivity	1 x 56Gb/s FDR InfiniBand QSFP
Storage Protocol	iSCSI/iSER, SRP NFS, CIFS/SMB
Management Interface	Web-based management interface (via HTTP/HTTPS) CLI (via serial port)
Power Supply	700W/750W 1+1 redundant
Feature Highlight	<ul style="list-style-type: none"> • Hot-swappable SSDs and PSUs • Data protection through redundancy • Affordable high performance in compact form factor
Dimensions (W x D x H)	437mm x 597mm x 43mm (17.2in x 23.5in x 1.7in)
Net Weight ²	12.7kg (28.0lb)
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing

¹ Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

² Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.

starline®
Computer GmbH

Carl-Zeiss-Str. 27-29 • D-73230 Kirchheim / Teck
Tel. +49(0)7021-487 200 • Fax +49(0)7021-487 400

www.starline.de



VC20170302