



NeoSapphire

NS3505 All-Flash Array

- A low TCO solution offering superior performance with 500K IOPS over InfiniBand FDR connectivity
- Easy maintenance with 10 hot-swappable SSDs and 2 PSUs
- Fault tolerance with automatic data reconstruction for a peace of mind





NeoSapphire 3505 All-Flash Array

SPECIFICATIONS


Form Factor	1U rack mount
IOPS for 4KB Random Write	500K sustained
Flash Management	FlexiRemap technology
Raw Capacity	9TB
Usable Capacity ¹	5TB
Number of SSD	10 x hot-swappable SSD
Flash Type	MLC
Connectivity	1 x 56Gb/s FDR InfiniBand QSFP
Storage Protocol	iSCSI/iSER, SRP NFS, CIFS/SMB
Management Interface	Web-based management interface (via HTTP/HTTPS) CLI (via serial port)
Power Supply	700W/750W 1+1 redundant
Feature Highlight	<ul style="list-style-type: none"> • High performance in compact form factor • Low-latency connectivity for HPC applications • Data protection through redundancy
Dimensions (W x D x H)	437mm x 597mm x 43mm (17.2in x 23.5in x 1.7in)
Net Weight ²	12.7kg (28.0lb)
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing

¹ Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

² Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.


starline[®]
 Computer GmbH
 Carl-Zeiss-Str. 27-29 • D-73230 Kirchheim / Teck
 Tel. +49(0)7021-487 200 • Fax +49(0)7021-487 400
www.starline.de



V20170302