




NeoSapphire P710

- Flagship model with superior performance with 700K IOPS
- Fault-tolerance with 24 hot-swappable SSDs, including 2 for hot spares
- Abundant software functions for different applications



NeoSapphire All-Flash Array



P710 All-Flash Array		SPECIFICATIONS
Form Factor	2U rack mount	
IOPS for 4KB Random Write	700K sustained	
Flash Management	FlexiRemap technology	
Raw Capacity	19TB/38TB	
Usable Capacity ¹	11TB/23TB	
Number of SSD	24 x hot-swappable SSD	
Flash Type	MLC	
Connectivity	6 x 10GbE SFP+ Or 4 x 16G Fibre Channel LC SFP+	
Storage Protocol	iSCSI NFS, CIFS/SMB Or Fibre Channel	
Management Interface	Web-based management interface (via HTTP/HTTPS) CLI (via serial port)	
Power Supply	920W 1+1 redundant	
Feature Highlight	<ul style="list-style-type: none"> • Outperforming IOPS via mainstream connectivity • Two SSDs for hot spares • Data protection through redundancy • Abundant options for software function 	
Software Function	<ul style="list-style-type: none"> • Free Clone • Snapshot • Snapshot Backup • Thin Provisioning • Thick Provisioning 	<ul style="list-style-type: none"> • Inline Deduplication (Zero Page) • vSphere Web Client Plug-in
Certification	<ul style="list-style-type: none"> • VMware Ready • VMware VAAI Block 	
Dimensions (W x D x H)	437mm x 630mm x 89mm (17.2in x 24.8in x 3.5in)	
Net Weight ²	19.8kg (43.7lb)	
Environmental Temperature	Operating: 10°C to 35°C (50°F to 95°F) Storage (non-operating): -20°C to 60°C (-4°F to 140°F)	
Environmental Humidity	Operating: 10% to 90% non-condensing Storage (non-operating): 5% to 95% non-condensing	

¹ Usable capacity refers to the approximation of the storage capacity that users can have. The accurate usable capacity may vary depending on software configurations and other factors.

² Weight may vary depending on components and manufacturing variability.

©2015-2017. All rights reserved. AccelStor, FlexiRemap, and NeoSapphire are trademarks or registered trademarks of AccelStor, Inc. in the United States of America and/or other countries. Other names and brands may be claimed as the property of others. Pictures are not contractual. In a continuing effort to improve the quality of our products, information in this brochure is subject to change without notice. Images appearing are only representations of some of the configurations available. Availability may vary depending on region. AccelStor, Inc. reserves the right to the interpretation of the above specifications, terms and conditions.

