

# netstor NS372TB3

1U Rackmountable 2-bay (5.25") LTO Tape Drive to Thunderbolt™ 3  
Enclosure



## Specifications

### NS372TB3

Host Interface	Thunderbolt™ 3 (Dual Port USB-C for Daisy Chain)
Data Transfer Rate	40Gbps
No. of LTO(s)	Up to 2 * 5.25-inch LTO Tape Driver
LTO Interface	SFF-8482 with integrated power
LTO size	210(D) x 134(W) x 42(H) mm 8.3(D) x 5.25(W) 1.65" (H) inch
Thunderbolt Expansion	Up to Six Thunderbolt devices
Fan Cooler	Two 75x 75x 28mm Blower (rear)
Power Supply	Server-grade 250W Single Power Supply Low-noise Design Universal: 100~240VAC, 50/60Hz
Enclosure Dimension	452(D) x 482(W) x 44(H) mm 17.8(D) x 19(W) x 1.73(H) inch
Operating System	Mac OS X 10.12.3 above Windows 10/8
Environmental Requirements	Operation Temperature: 5°C ~ 50°C Storage Temperature: -20°C~ 70°C Operation Humidity: 10% ~ 80%, non-condensing Storage Humidity: 5% ~ 95%
Package Content	1U Enclosure x 1 Thunderbolt3-40Gbps cable x 1 (1 meter) Power Cord x 1

